



# ELITE EVOLUTION C4 5W-30

## Description

ACEA C4 quality synthetic lubricant oil, specially recommended in vehicles with particle filters and exhaust fume treatment. It stands out for its low ash formation (Low SAPS), and it is most adequate for Renault diesel vehicles that require RN0720 quality level. It is also a long-lasting lubricant, allowing significant extension of oil change intervals; always according to the manufacturer's recommendations. Its performance levels mean that it can be used in vehicles that require ACEA C3 or ACEA C4.

## Properties

- Its reduced ash content (Low SAPS) makes it essential for ensuring the durability of new technologies applied to reduce pollutant emission levels, such as diesel particle filters (DPF).
- The RN0720 quality level ensures high oil resistance to oxidation and a minimum formation of deposits in the piston, thus extending the oil change period.
- Contributes to reducing CO2 emissions, obtaining fuel savings of up to 1 % compared to other lubricants under standard M111FE test conditions.

## Quality levels, approvals and recommendations

- MB: 226.51\*
- ACEA: C4
- RENAULT: RN0720\*
- FIAT: Meets FIAT 9.55535 S4

\*Formal approval

## Technical specifications

|                               | UNIT     | METHOD     | VALUE  |
|-------------------------------|----------|------------|--------|
| SAE Grade                     |          |            | 5W-30  |
| Density at 15 °C              | g/cm3    | ASTM D4052 | 0.850  |
| Kinematic viscosity at 100 °C | cSt      | ASTM D445  | 12.2   |
| Kinematic viscosity at 40 °C  | cSt      | ASTM D445  | 71     |
| CCS Viscosity at -30 °C       | cP       | ASTM D5293 | <6,600 |
| Viscosity index               |          | ASTM D2270 | 168    |
| Flash point, open cup         | °C       | ASTM D92   | >200   |
| Pour point                    | °C       | ASTM D97   | -45    |
| TBN                           | mg KOH/g | ASTM D2896 | 8.2    |

The above mentioned characteristics are typical values and should not be considered product specifications.