PENNZOIL PLATINUM® SAE 0W-20 FULL SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Pennzoil Platinum® is designed to protect your pursuit of every mile, for the life of your engine. Backed by both our 15,000-mile protection guarantee*,** and our 15-year, 500,000-mile warranty**, we've got you covered between oil changes and for the long run. This premium oil offers cleaner pistons[1,] protected horsepower, better fuel economy[2,] and excellent performance in extreme temperatures. It all adds up to complete protection—mile after thrilling mile.

1 Based on ILSAC GF-7A Sequence IIIH piston deposit test results. Does not apply to SAE 0W-16 or Pennzoil Platinum® Euro motor oil.
2 Based on ILSAC GF-7 Sequence VIE fuel economy Test.
*Limited Lubrication Warranty of engine protection up to 15 years or 500,000 miles, whichever comes first, and oil drain interval protection of 15,000 miles or one year, whichever comes first, if you (1) switch to and exclusively use Pennzoil Platinum® Full Synthetic motor oils; and (2) follow all oil change recommendations in your owner's manual. For oil drain interval protection, you must use an oil filter designed for longer oil change intervals and follow OEM manual and vehicle's oil life sensor to maintain OEM warranty. Your engine must have fewer than 125,000 miles and have been manufactured in the past 72 months. Other conditions apply, including enrollment and receipt requirements. See full details and enroll at pennzoil.com/warranty

PERFORMANCE, FEATURES & BENEFITS

Pennzoil® is designed to maximize engine protection for top engine performance.

- CLEANER PISTONS

Helps keep pistons cleaner than required by the toughest industry standard.[1]

- BETTER FUEL ECONOMY.[2]
- PROTECTS HORSEPOWER

Helps protect engines from loss of power.

- WEAR PROTECTION

Helps provide protection from friction[3]

- EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES

Provides faster low temperature oil flow and protects in extreme heat

1 Based on ILSAC GF-7A and Sequence IIIH piston deposit test
2 Based on Sequence VIE fuel economy test
3 Based on Sequence IVB wear test

MAIN APPLICATIONS

- Pennzoil Platinum® SAE 0W-20 is recommended for use in all vehicles requiring the use of SAE 0W-20 viscosity grade engine oils under all driving conditions.
- SAE 0W-20 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology for maximum fuel economy and performance.
- Pennzoil Platinum® SAE 0W-20 is also suitable for use and offers the same protection as SAE 5W-20.
- Pennzoil Platinum® can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

© SOPUS Products 2026. All rights reserved.

PENNZOIL PLATINUM® SAE 0W-20 FULL SYNTHETIC MOTOR OIL

- Pennzoil Platinum® 0W-20 is designed to provide enhanced fuel economy and provides the same engine protection for use in vehicles currently using SAE 5W-20.
- SAE 0W-20 may not be suitable for use in older engines, so always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Meets or exceeds the requirements of the following industry and OEM specifications:

- API SQ-Resource Conserving and all previous categories
- ILSAC GF-7A and all previous ILSAC Standards
- Chrysler MS-6395
- Ford WSS-M2C972-A1

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	PENNZOIL PLATINUM® SAE 0W-20 FULL SYNTHETIC MOTOR OIL
Viscosity Grade				0W-20
Service Category				SQ-RC
ILSAC				GF-7A
Density		kg/m^3	ASTM D4052	836
Flash Point		^0C	ASTM D93	204
Pour Point		^0C	ASTM D97	-33
Kinematic Viscosity	@ 40^0C	cSt	ASTM D445	43.4
Kinematic Viscosity	@ 100^0C	cSt	ASTM D445	8.6
Viscosity Index			ASTM D2270	182
CCS Viscosity	@-35^0C	cP	ASTM D5293	5 670
MRV Viscosity	@-40^0C	cP	ASTM D4684	16 200

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

- Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from https://www.epc.shell.com

- Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

- Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or technical helpdesk.

© SOPUS Products 2026. All rights reserved.